


# STA 160

Very reliable product  
 Full range of colors from 1800K to 6500K  
 SDCM<3 CRI>90  
 3M double-sided tape



**STA 14W 160 IP20 . 927**

Model Power LED nr. IP grade CCT

Model	CCT	
STA	927	2700K
	930	3000K
Power	940	4000K
14W [W/m]	950	5000K
	960	6000K

**LED Nr.**  
160 [led/m]

**IP grade**  
 IP20  
 IP65  
 IP67  
 IP68

## Accessories

Connection kit IP67 (white strip)	ACC00028
Set off 5 mounting clips	ACC00029

## Features

LED type	SMD2835
LED nr.	160LEDs/m
Standard CCT	2700K/3000K/4000K/5000K/6000K
Other CCT upon request	1800K/2100K/2300K/6500K
Beam angle	120°

## Performance

Lumen output (at 85°C)	1442 – 1696lm/m (439– 517lm/ft)
Color rendering index	>90
Efficacy	100 – 118lm/W

## Electrical and control

Supply type	Constant voltage
Input voltage	DC24V
Input current	0.6A/m (0.18A/ft)
Max. power consumption	14.4W/m (4.39W/ft)
Dimming	External

## Physical

Minimum cut	50mm (1.97")
Reel length	5m (16.40')
Weight	0.05kg/m
Operating temperature	-25/+55°C
ESD Protection	+/- 2000V

