


# COM 01

Anti-glare design  
 Different power options  
 SDCM<3 CRI>90  
 Suitable for general lighting

**C01 . 06W 015 B IP20 927**

Model Power Beam angle Body color IP grade CCT

<b>Model</b>	<b>IP grade</b>
COM	IP20
<b>Power</b>	<b>CCT</b>
06W [W]	927 2700K
09W [W]	930 3000K
	940 4000K
<b>Beam angle</b>	950 5000K
015 [°]	
024 [°]	
035 [°]	
055 [°]	
<b>Body color</b>	
B Black	
W White	



<b>Features</b>	
LED type	CREE
Color and CCT	2700K/3000K/4000K/5000K
Other colors	Upon request
Beam angle	15°/24°/35°/55°
<b>Performance</b>	
Max. delivered output	500lm (6W) / 700lm (9W)
Efficacy	83lm/W (6W) / 78lm/W (9W)
<b>Electrical and control</b>	
Supply type	Main voltage (Integral LED driver)
Input voltage	AC240V
Max. power consumption	6W/9W
Dimming	Upon request
<b>Physical</b>	
Cut out	75mm
Housing material	Aluminium
Optics material	PMMA
Weight	-
Operating temperature	-25/+55°C
<b>Accessories</b>	
Matt black reflector	ACC00101
Titanium reflector	ACC00102
Bright silver reflector	ACC00103
Matt silver reflector	ACC00104
Matt white reflector	ACC00105
Honeycomb D40	ACC00106
Smooth filter D40	ACC00107

<b>WW</b>	<b>NW</b>	<b>CW</b>					
<b>AC 240V</b>	<b>CRI &gt;90</b>	<b>SDCM &lt;3</b>	<b>LM80</b>		<b>IP20</b>		