


COM 02

Anti-glare design
 Different power options
 SDCM<3 CRI>90
 Suitable for general lighting

C02 . 12W 015 B IP20 927

Model Power Beam angle Body color IP grade CCT

Model	IP grade	
COM	IP20	
Power	CCT	
12W [W]	927	2700K
15W [W]	930	3000K
	940	4000K
Beam angle	950	5000K
015 [°]		
024 [°]		
035 [°]		
055 [°]		
Body color		
B <i>Black</i>		
W <i>White</i>		



Features

LED type	CREE
Color and CCT	2700K/3000K/4000K/5000K
Other colors	Upon request
Beam angle	15°/24°/35°/55°

Performance

Max. delivered output	1000lm (12W) / 1300lm (15W)
Efficacy	83lm/W (12W) / 87lm/W (15W)

Electrical and control

Supply type	Main voltage (Integral LED driver)
Input voltage	AC240V
Max. power consumption	12W/15W
Dimming	Upon request

Physical

Cut out	75mm
Housing material	Aluminium
Optics material	PMMA
Weight	-
Operating temperature	-25/+55°C

Accessories

Matt black reflector	ACC00108
Titanium reflector	ACC00109
Bright silver reflector	ACC00110
Matt silver reflector	ACC00111
Matt white reflector	ACC00112
Honeycomb D40	ACC00113
Smooth filter D40	ACC00114

