


# MIN 03

Compact size  
Power up to 4.5W  
SDCM<3 CRI>90

**M03.02W 020 B IP20 927**

Model Power Beam angle Body color IP grade CCT

|                   |                 |
|-------------------|-----------------|
| <b>Model</b>      | <b>IP grade</b> |
| MIN               | IP20            |
| <b>Power</b>      | <b>CCT</b>      |
| 02W [W]           | 927 2700K       |
| 03W [W]           | 930 3000K       |
|                   | 940 4000K       |
| <b>Beam angle</b> | 950 5000K       |
| 020 [°]           |                 |
| 038 [°]           |                 |
| 060 [°]           |                 |
| <b>Body color</b> |                 |
| B Black           |                 |
| W White           |                 |



## Features

|               |                         |
|---------------|-------------------------|
| LED type      | CREE                    |
| Color and CCT | 2700K/3000K/4000K/5000K |
| Other colors  | Upon request            |
| Beam angle    | 20°/38°/60°             |

## Performance

|                       |                               |
|-----------------------|-------------------------------|
| Max. delivered output | 225lm (2W) / 400lm (3.5W)     |
| Efficacy              | 113lm/W (2W) / 114lm/W (3.5W) |

## Electrical and control

|                        |                                    |
|------------------------|------------------------------------|
| Supply type            | Main voltage (Integral LED driver) |
| Input voltage          | AC240V                             |
| Max. power consumption | 2W/3.5W                            |
| Dimming                | Upon request                       |

## Physical

|                       |           |
|-----------------------|-----------|
| Cut out               | 45mm      |
| Housing material      | Aluminium |
| Optics material       | PMMA      |
| Weight                | -         |
| Operating temperature | -25/+55°C |

